(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 23 June 2005 (23.06.2005)

PCT

(10) International Publication Number WO 2005/056705 A1

(51) International Patent Classification⁷: C09D 175/04, 7/12

(21) International Application Number:

PCT/JP2004/018955

(22) International Filing Date:

10 December 2004 (10.12.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 2003-414369

12 December 2003 (12.12.2003) JI

- (71) Applicants (for all designated States except US): SANYO CHEMICAL INDUSTRIES, LTD. [JP/JP]; 11-1, Ikkyo Nomotocho, Higashiyama-ku, Kyoto-shi, Kyoto 6050995 (JP). ТОУОТА JIDOSHA KABUSHIKI KAISHA [JP/JP]; 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): SHINDO, Yasuhiro [JP/JP]; c/o Sanyo Chemical Industries, Ltd., 11-1, Ikkyo Nomotocho, Higashiyama-ku, Kyoto-shi, Kyoto 6050995 (JP). FURUTA, Takeshi [JP/JP]; c/o Sanyo Chemical Industries, Ltd., 11-1, Ikkyo Nomotocho, Higashiyama-ku, Kyoto-shi, Kyoto 6050995 (JP). YAMAMOTO, Yusuke [JP/JP]; c/o Sanyo Chemical Industries, Ltd., 11-1, Ikkyo Nomotocho, Higashiyama-ku, Kyoto-shi, Kyoto 6050995 (JP). KUWANO, Kazuyuki [JP/JP]; c/o Toyota Jidosha Kabushiki Kaisha, 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP). NARITA, Yoshinori [JP/JP]; c/o Toyota Jidosha Kabushiki Kaisha, 1, Toyota-cho, Toyota-shi, Aichi dosha Kabushiki Kaisha, 1, Toyota-cho, Toyota-shi, Aichi

4718571 (JP). TACHI, Kazuyuki [JP/JP]; c/o Kabushiki Kaisha Toyota Chuo Kenkyusho, 41-1, Aza Yokomichi, Oaza Nagakute, Nagakute-cho, Aichi-gun, Aichi 4801192 (JP).

- (74) Agent: FURUTANI, Shinya; Furutani Naigai Tokkyo Jimusho, 1-27, Dojima 2-chome, Kita-ku, Osaka-shi, Osaka 5300003 (JP).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCI Gazette.

(54) Title: WATER-DISPERSED SLURRY COATING

(57) Abstract: This invention relates to a water-dispersed slurry coating which can provide a film excellent in water resistance and strength. The water-dispersed slurry coating comprises: (A) a particulate comprising (a1) a resin having an active hydrogen; and (B) a reactive surfactant comprising a hydrophilic moiety and a hydrophobic moiety having an aromatic ring-containing hydrocarbon group having 6 to 100 carbon atoms and having at least one group selected from the group consisting of an isocyanate group, a blocked isocyanate group and an epoxy group in the hydrophilic moiety, and having an oxyethylene group in a content of not less than 20 % and not more than 97 % by weight; and (a2) a curing agent according to need, in aqueous medium.

